


POP-UP 3



Light output: up to 1512lm **Cut out:** ø90mm **Standard finishing:** ● ○

Features

Showcasing our POP-UP 3, featuring a lumen output of 1250lm to 1512lm. Available in standard color temperatures of 2700K, 3000K, and 4000K, with additional options on request. This versatile product offers various beam angles ranging from 15° to 50°, making it ideal for retail and art gallery spaces. With an IP20 rating, it provides suitable protection for indoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

Dimming options

For dimmable version add the following suffix to the Part number → -1V: 1-10V, -DA: DALI, -PU: Push, -TR: Triac.

Applications

POP-UP adjustable recessed projectors are perfect solutions for lighting up retail spaces, art galleries, and car showrooms. The high CRI ensures colours are seen in their natural, vivid forms. Their extreme adjustability and the ability to retract the bodies completely offer great flexibility and adaptability, making them ideal for quick changes in settings. This makes POP-UP versatile and efficient solutions for environments that require frequent transformations.



POP-UP 3 - 15W

	Optics	Output	CCT	Part number
□ refers to finishing: B: Black, W: White. Other CCT upon request.	10°	1260lm	2700K	A109.15W010□927
		1361lm	3000K	A109.15W010□930
		1512lm	4000K	A109.15W010□940
	24°	1255lm	2700K	A109.15W024□927
		1355lm	3000K	A109.15W024□930
		1506lm	4000K	A109.15W024□940
	38°	1251lm	2700K	A109.15W038□927
		1351lm	3000K	A109.15W038□930
		1501lm	4000K	A109.15W038□940
	50°	1250lm	2700K	A109.15W050□927
		1350lm	3000K	A109.15W050□930
		1500lm	4000K	A109.15W050□940