


POP-UP 4



Light output: up to 2620lm **Cut out:** ø120mm **Standard finishing:** ● ○

Features

Showcasing our POP-UP 4, featuring a lumen output of 2166lm to 2620lm. Available in standard color temperatures of 2700K, 3000K, and 4000K, with additional options on request. This versatile product offers various beam angles ranging from 15° to 60°, making it ideal for retail and art gallery spaces. With an IP20 rating, it provides suitable protection for indoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

Dimming options

For dimmable version add the following suffix to the Part number → -1V: 1-10V, -DA: DALI, -PU: Push, -TR: Triac.

Applications

POP-UP adjustable recessed projectors are perfect solutions for lighting up retail spaces, art galleries, and car showrooms. The high CRI ensures colours are seen in their natural, vivid forms. Their extreme adjustability and the ability to retract the bodies completely offer great flexibility and adaptability, making them ideal for quick changes in settings. This makes POP-UP versatile and efficient solutions for environments that require frequent transformations.



POP-UP 4 - 25W

	Optics	Output	CCT	Part number
□ refers to finishing: B: Black, W: White. Other CCT upon request.	15°	2183lm	2700K	A110.25W015□927
		2358lm	3000K	A110.25W015□930
		2620lm	4000K	A110.25W015□940
	24°	2174lm	2700K	A110.25W024□927
		2348lm	3000K	A110.25W024□930
		2609lm	4000K	A110.25W024□940
	38°	2168lm	2700K	A110.25W038□927
		2341lm	3000K	A110.25W038□930
		2601lm	4000K	A110.25W038□940
	60°	2166lm	2700K	A110.25W060□927
		2339lm	3000K	A110.25W060□930
		2599lm	4000K	A110.25W060□940