


POP-UP 5



Light output: up to 3577lm **Cut out:** ø140mm **Standard finishing:** ● ○

Features

Showcasing our POP-UP 5, featuring a lumen output of 2957lm to 3577lm. Available in standard color temperatures of 2700K, 3000K, and 4000K, with additional options on request. This versatile product offers various beam angles ranging from 15° to 60°, making it ideal for retail and art gallery spaces. With an IP20 rating, it provides suitable protection for indoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

Dimming options

For dimmable version add the following suffix to the Part number → -1V: 1-10V, -DA: DALI, -PU: Push, -TR: Triac.

Applications

POP-UP adjustable recessed projectors are perfect solutions for lighting up retail spaces, art galleries, and car showrooms. The high CRI ensures colours are seen in their natural, vivid forms. Their extreme adjustability and the ability to retract the bodies completely offer great flexibility and adaptability, making them ideal for quick changes in settings. This makes POP-UP versatile and efficient solutions for environments that require frequent transformations.



POP-UP 5 - 35W

	Optics	Output	CCT	Part number
□ refers to finishing: B: Black, W: White. Other CCT upon request.	15°	2981lm	2700K	A111.35W015□927
		3220lm	3000K	A111.35W015□930
		3577lm	4000K	A111.34W015□940
	24°	2969lm	2700K	A111.35W024□927
		3207lm	3000K	A111.35W024□930
		3563lm	4000K	A111.35W024□940
	38°	2960lm	2700K	A111.35W038□927
		3197lm	3000K	A111.35W038□930
		3552lm	4000K	A111.35W038□940
	60°	2957lm	2700K	A111.35W060□927
		3194lm	3000K	A111.35W060□930
		3549lm	4000K	A111.35W060□940