

SPOT-R 3



Features


Showcasing our SPOT-R 3, featuring a lumen output of 2124lm to 2570lm. Available in standard color temperatures of 2700K, 3000K, and 4000K, with additional options on request. This versatile product offers various beam angles ranging from 15° to 55°, making it ideal for commercial location. With an IP20 rating, it provides suitable protection for indoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.


Dimming options


For dimmable version add the following suffix to the Part number → -1V: 1-10V, -DA: DALI, -PU: Push, -TR: Triac.


Applications


SPOT-R downlights are the ideal combination of simplicity, durability, and functionality with our downlights, perfectly suited for all your general lighting needs. Whether you require efficient illumination for expansive spaces, sleek lighting solutions for retail environments, or optimal settings for meeting rooms, these downlights are designed to deliver it. They provide effective, uniform lighting while minimizing visual impact, allowing them to integrate seamlessly into any environment. Ideal for offices, commercial spaces, and public areas, these downlights offer reliable and enduring lighting solutions.






























SPOT-R 3 - 24W

	Optics	Output	CCT	Part number
□ refers to finishing: B: Black, W: White. Other CCT upon request.	15°	2141lm	2700K	A030.24W015□927
		2313lm	3000K	A030.24W015□930
		2570lm	4000K	A030.24W015□940
	24°	2133lm	2700K	A030.24W024□927
		2303lm	3000K	A030.24W024□930
		2559lm	4000K	A030.24W024□940
	35°	2133lm	2700K	A030.24W035□927
		2303lm	3000K	A030.24W035□930
		2559lm	4000K	A030.24W035□940
	55°	2124lm	2700K	A030.24W055□927
		2294lm	3000K	A030.24W055□930
		2549lm	4000K	A030.24W055□940

Accessories

Description	Part number
Frosted glass	ACC01187