


# SUN-P 3



**Light output:** up to 6863lm **Standard finishing:** ● ○

## Features

Presenting our SUN-P 3, featuring a lumen output of 5719lm to 6863lm. Available in standard color temperatures of 3000K, 4000K, and 5000K, with additional options on request. This product offers a 90° down and 120°up beam of light, making it ideal for inviting living areas. With an IP20 rating, it provides suitable protection for indoor environments. Additionally, we provide customized finishing options to meet the project specific requirements.

## Dimming options

For dimmable version add the following suffix to the Part number → -1V: 1-10V, -DA: DALI, -PU: Push, -TR: Triac.

## Applications

SUN-P pendant fixtures are powerful lighting solutions designed for large spaces, offering expansive, diffuse illumination that enhances both commercial and residential environments. Ideal for high-ceiling areas, they provide efficient lighting while adding warmth and elegance. Whether illuminating spacious retail areas, open-concept lofts, grand dining rooms, or expansive living spaces, SUN-P pendants create welcoming atmospheres. Their ability to produce direct and indirect light ensures each space is beautifully lit and infused with warmth and sophistication. Perfect for modern interiors, they transform ordinary spaces into extraordinary ones.



**SUN-P 3 - 53W**

Optics	Output	CCT	Part number
Up: 120° Down: 90°	1775lm 3944lm	3000K 3000K	N005.053WDFF□930
Up: 120° Down:90°	1917lm 4260lm	4000K 4000K	N005.053WDFF□940
Up: 120° Down:90°	2130lm 4733lm	5000K 5000K	N005.053WDFF□950

□ refers to finishing:  
B: Black, W: White.  
Standard configuration:  
1.5m steel wire set.  
Other CCT upon request.

**Accessories**

Description	Part number
3m steel wire set	ACC01168
5m steel wire set	ACC01169